


XK785Y

TION	Polyester	XK785Y	60
VSM	Polyester	XK785Y	60
	Polyester	XK785Y	60
SM	Polyester	XK785Y	60
and the second	Polyester	XK785Y	60
	Polyester	A REAL PROPERTY.	60
	THE R. P. LEWIS CO., LANSING MICH.	XK785Y	60
と見ている方で	Polyester	XK785Y	60
	alyester	XK785Y	60
	ester	XK785Y	60 60
	er	XK785Y	60
and the second		XK785Y	60
		K785Y	60
Self La Prop		85Y	60
	and the second	Y	60
2122 2154	100 C		60
CONTRACTOR OF STATE	See Second		60
	and the second	1000	

VSM CERAMICS Plus

Grain type	Ceramic
Bonding	Full-resin bonded
Colour	Red-violet
Backing	Y-Polyester
Flexibility	Very sturdy
Production width	1,480 mm

Materials Unaloyod Steel Steel



Thanks to its very robust backing, this product is particularly well suited for high contact pressures and demanding grinding tasks such as bevelling. Ideal for grinding unalloyed steel. The microcrystalline ceramic grain with optimised self-sharpening effect ensures maximum stock removal performance. Ideal alternative to XK885Y if the TOP SIZE additional layer is not required.


Grit range:1)



Benefits

- Optimised self-sharpening effect results in an extremely high stock removal rate thanks to constant recreation of sharp grain points
- Cost saving when grinding high-alloyed steels thanks to highest possible stock removal rate
- > Extremely long service life
- > High wear resistance

Wear pattern of the grain



t=O

Due to their optimised and thus finer microcrystalline structure, **VSM CERAMICS Plus** series feature an improved self-sharpening effect, which produces much more sharper edges

VSM · Vereinigte Schmirgel- und Maschinen-Fabriken AG Siegmundstraße 17 · 30165 Hanover · Germany T +49 511 3526 479 · F +49 511 3521 315 sales@vsmabrasives.com · www.vsmabrasives.com





Grinding time